## 4000 Surge Watts 3500 Running Watts

## **Tri Fuel Generator**




## GAS, LP, NG

Runs on Natural Gas, LPG or Unleaded Gasoline

- 4 x 120 Volt A/C Outlets
- 1 x 12 Volt D/C Outlet
- 1 x 120 Volt RV Outlet
- Oil SAE 10W30
- Oil Capacity: 18.5 oz.
- 120 Volt / 60 Hz
- 3.6 Gallon Fuel Tank
- Automatic Low Oil Shutdown
- Noise Level: < 69 dB @ 0% Load</li>
- 212cc OHV, 4 Stroke Air Cooled
- Fuel Type: Unleaded Gasoline Only 87 rating or higher
- This portable generator is not for use with gasoline/ ethanol blends with over 15% ethanol. Do not use E85 fuel.
- Run Time: 10 Hours at 50% Load (GAS)
- Run Time: 12 hours @ 50% Load (LPG) on 20 lbs of LPG Fuel
- Propane fuel hose / regulator included
- High Altitude Use: This generator is not recommended for high altitude use above 3,000 feet.
- If you are using a generator at 3,000 feet above sea level, the generator may not function properly because of air flow getting through the carburetor.
- SURGE WATTS / RUNNING WATTS MAY BE REDUCED BY 10% WHEN USING PROPANE FUEL VS USING GASOLINE.
- SURGE WATTS / RUNNING WATTS MAY BE REDUCED BY 20% WHEN USING NATURAL GAS VS USING GASOLINE









ATTENTION

A CO
WARNING

**ALERT!** 

This generator includes a built-in Carbon Monoxide Warning Alert! The generator will automatically shut-off if dangerous levels of Carbon Monoxide is detected.

AWARNING Carbon monoxide (also known as CO) can be dangerous for humans and pets. Carbon monoxide poisoning can lead to death in a very short time. It is called "the silent killer" because it is odorless, tasteless and invisible: you may be exposed without knowing it.

NOTE: The indicator will light RED and the engine will shutdown if dangerous Carbon Monoxide levels are detected. The engine will not restart for 5 minutes. If an error in the carbon monoxide system is detected, the indicator will blink YELLOW and the engine will shutdown for five minutes.



AUTOMATIC SHUTOFF - YOU MUST:



**+** 0

MOVE TO FRESH AIR AND GET MEDICAL HELP IF SICK, DIZZY OR WEAK. MOVE GENERATOR TO AN OPEN, OUTDOOR AREA. POINT EXHAUST AWAY. DON'T RUN GENERATOR IN ENCLOSED AREA (F. G. DOI'T IN HOUSE OR CAPAGE'A)

Package: 2-Color Box

Item No. UPC Case Wt. Cubic Ft. Case Qty.

GEN4000TRI 0 27077 07839 8 97.0 lbs 5.34 1

950 Hoff Road

**O'Fallon, MO 63366** 

Phone 636.532.9888

Fax 636.537.1055